

*Specify
‘FSI Blue’®*

**FSI® DAT® 3030S Two Line Non-Ambulatory
Mass Casualty Decon Shower System**



The DAT®3030S comes equipped as standard equipment with an integrally attached ground floor that will hold up to 200 gallons of water (with an 8”/20 cm berm approx.) before requiring pump out, 2 roll up windows – one on each side, 2 skylights, full closure slip in and out dirty entry/clean exit doors, eight 19”/48 cm dia HVAC/clothes inlet/outlets with tie closures – 2 each on each end/side, 1 small electrical duct, 1 center divider curtain, 2 (two) ½ cross divider curtains, 1 ea. high pressure and low pressure inflation deflation valve, one air inflation hose w. safety cord, 1 pressure relief valve, 4 metal stakes, hammer and ground anchor points, tie down ropes and 4 D-rings to tie off to, repair kit, manual, shelter sleeve, 2 upper air vents. All canopy walls are velcro’d to the floor air berms for air lock, and reflective striping is found on the upper air vents above doors and on entry and exit integral shower stall air berms. Units can attach to a second shower or FSI® shelter. Simply inflate the unit - plug into a water supply and commence decon in 1 – 2 minutes.

The DAT®3030S also comes complete with a with a qty. of 12 spray nozzle heads and qty. of 4 (four) 5’/1.5 M lengths of coiled ½”/13 mm hose with attached multiple function spray guns with shutoffs and quick disconnects offering spray patterns and flows meant to gently yet thoroughly drench and decon victims. Flows per shower head and per spray gun = approx. 1 gpm/4 lpm optimum and dependent on water volumes available.

The DAT®3030S is a 2 (two) line system designed to handle 2 non-ambulatory personnel on stretchers with attendants working on either side of the victim inside the unit, or the DAT3030S can handle 1 non-ambulatory and two ambulatory, or 4 ambulatory personnel at any one time.

DAT®3030S Approx. 10’ W X 10’ L X 9’ H (3.05 X 3.05 X 2.73 M), Approx. 100 sq. Ft. (9.3M²) 139 lbs. (63 Kg) Carton size approx. = 131 X 108 X 68 cm (52” L X 43” W X 27” H) As an option -- one can double the capacity if required. Simply inflate the unit and plug into a water supply - unit is offered with 2 3/4” (19mm) GHT threaded inlet hose– other fittings available as specified. Comes complete with electric inflator/deflator, and high pressure scba fitting. Unit supplied w. no charge redundant features allowing for - hanging undress/redress kits etc. on the inlet and outlet side and - doubling of showering capability in the future.

Multiple optional accessories available inclusive of air and water heaters, air coolers, elevation grids, waste water pumps, etc. available – Visit: www.fsinorth.com

All FSI® decon showers are ANSI # 113 compliant

In accordance with **NFPA 1851** all FSI Showers are ideal for fire fighter wash down/decon immediately after exiting fire scene and prior to removal of any PPE.

*** All FSI Show-proved Hose manufactured with Texin 985U (formerly DP7-1077) or Texin 1209 which are approved by NSF. This polyurethane is approved for “Potable Water” use by NSF International (NSF Standard 61 – Drinking Water System Components – Health Effects).

ers utilize Potable systems. These

Water ap-hoses are

FSI shelters help ensure compliance with the OSHA Heat Illness requirement as described at:
https://www.osha.gov/OshDoc/data_Hurricane_Facts/heat_stress.pdf

