



- Model F-UPEW 14
 - Total Height: 13"/ 330 mm
 - Box Dimension: 24" x 12" x 16 1/2"
 - Net Weight: 10 lbs. / 4.5 kg Gross Weight: 13 lbs. / 5.75 kg.
 - Package: 1 unit per Box
- Description > FSI Portable Eyewash
 - Self contained unit provides 15 minutes of decontaminating water
 - 34 liter/9 gallon capacity for easier transport
 - Small compact size with carry handle for ease of portability and transport
 - Chemical resistant high density polyethylene material construction
 - Large fill cap for ease of filling, cleaning and inspection
 - Eye wash activated by simply pulling the retractable tray
 - Retractable tray protects against air borne contaminants
 - High visibility colors
 - Mounting bracket supplied – simply bolt to wall
 - Additive not included and priced P.O.A.



- Model F-LSE-2 GI
 - Total Height: 42"/ 1067 mm
 - Box Dimension: 31" x 12" x 8 1/2"
 - Net Weight: 44 lbs. / 20 kg. Gross Weight: 51 lbs. / 23 kg.
 - Package: 2 units per Box
- Description > FOOT-PEDAL operated Eye/Face Wash Station features
 - Twin cushion flow atomizers with pop-off dust covers
 - Automatic flow compensators
 - Impact/corrosion resistant ABS plastic receptor
 - 1/2" Gun metal/brass valve with Stainless Steel ball and spindle
 - 'C' class heavy duty galvanized pipes 4.05mm wall thickness with pedestal
 - Supply 1 1/4", Drain 1 1/4"
 - Recommended Pressure : 30 psi



- Model F-LSE -1 CSS
 - Total Height: 42"/1067mm
 - Box Dimension: 31" x 12" x 8 1/2"
 - Net Weight: 38 lbs. / 17 kg Gross Weight: 42 lbs. / 19 kg.
 - Package: 2 units per Box
- Description > PUSH-LEVER operated Eye/Face Wash Station features:
 - Stainless Steel Twin cushion flow atomizers with pop-off dust covers
 - Automatic flow compensators
 - # 304 stainless steel receptor
 - 1/2" stainless steel valve with stainless steel ball and spindle
 - Supply 1 1/4", Drain 1 1/4"
 - Recommended Pressure : 30 psi

> FSI PRE-PLUMBED WALK ON ACTIVATED, DECONTAMINATION SAFETY SHOWER SYSTEMS



● Model F-LMNS-10

16 NOZZLE DECONTAMINATION UNIT OPERATED BY WALK - ON - PLATFORM AND/OR SINGLE SUPPLIED VALVE.

Designed to be located in high hazard areas where space is limited. They can be mounted against a wall for e.g.

The unit consists of 16 self - cleaning spray nozzles that provide overall body saturation within a matter of seconds.



● Model F-LMNS-11

Shower is activated with instant action Ball valve with easy - to - locate Yellow ABS Plastic Push - plate.

Designed to be located in high hazard areas where space is limited. They can be mounted against a wall for e.g.

The unit consists of 16 self - cleaning spray nozzles that provide overall body saturation within a matter of seconds.

FEATURES:

- Impact/corrosion resistant ABS Plastic spray shower heads
- 1" Gun metal/brass valve with stainless steel ball and spindle
- 'C' class heavy duty galvanized pipes 4.05 mm wall thickness
- Recommended Pressure : 30 psi

Model No	Total Height of the unit	Box dimension	Net wt.	Gross Wt.	Qty / box
F-LMNS-10	7.5 ft./ 2286 MM	48" X 35" X 5"	77 lbs./ 35 KG	93 lbs./ 42 KG	01
LMNS-11	7.5 ft./ 2286 MM	48" X 35" X 5"	55 lbs./ 25 KG.	69 lbs./ 31 KG.	01

Approvals : ANSI Z 358.1 all editions compliant