

TECHNICAL DATA:

F-BDEC601

Approx. External Dimensions:

48" (120cm) X 48" (120cm) X 87" (220cm)

Materials:

High quality SS304 stainless steel frame and shower heads.

Canopy: Heavy duty 100% nylon twill (3/5) w. PU white pigment inner coating, ABT. 0 23mm X 57/58. Wt. AB1.230GR/Sq. M - UV/chemical resistant/fire retardant - Rated Ultra Violet Protection (UPF) of 50+ where ASTM D6603 states a UPF of 40+ is rated Excellent; and water repellent w. a hydrostatic resistance of 250 psi + - Anti fungus/Mildew resistant to meet and exceed US Fed. Test MIL.STD.810E 508 and ASTM G 21-96 (2002); Water Resistance (ISO 811 (E) 1981, hydrostatic pressure test at water pressure 600 m/min. = 5540; Tensile Strength (ISO 13934-2: 1999 C.R.E. Method in N) - warp = 1300 - weft = 1500; Tear Strength (ISO 13937-1:2000, Pendulum method) - Warp = 25 Weft = 43; Burst Strength (ASTM 0 3787:2001, C.R.E. Ball bursting method N) = 1620; Seam Strength (ISO 13935-2: 1998, Grab method N) Sewing threads fail at 710; Fire resistance meets and exceeds CPAI 84 SECTION 5 1995, US Fed. Test CFR.1610, meets NFPA701 Flammability Test method 1 (2004), NFPA 702 w. 'A' burn scale rating, Japan JIS A 1322: 1966, Method A. All seams double stitched and coated both sides.

Floor: 1,000 dtex 0.58mm Nylon coated w. PU, tensile strength: 2545N/2360, Tear Strength: 106/102N, weight: 660 grams per sq. mm 60" W.

Water Inlet:

1.25" Female NPT (31.25mm)

Pressure:

Operates from 50 psi (3.4bar) - 150 psi (10 bar) inlet through 5 nozzles capable of water pressure.

Flow Rate:

Through 5 nozzles capable of a water flow of approx. 3 gpm each at 50 psi (3.34 bar), inlet water pressure and of providing high pressure water mist at up to 150 psi (10 bar) for equipment and chem. suit decon.

ANSI Z358.1-2014 COMPLIANT