

TRACE HEATED FREEZE PROTECTED DRENCH SHOWER/EYE WASH STATIONS



- Model
- Description

F-580

Trace Heated Freeze Protected Drench Shower/Eye Wash technical data:

The F-580 provides effective protection in areas exposed to -25 C/-13 F. Heat trace tape is applied directly to the interior piping which is further surrounded by polyurethane insulation and a poly fiber outer sleeve for added thermal protection.

Shower Head/Eyewash: 10" ABS plastic of Safety Yellow color

Valves: 1" corrosion-resistant 304SS ball valve. Eyewash valve of 1/2" corrosion-resistant 304SS ball valve.

Water supply: 1" IPT. **Water outlet:** 1 1/4" IPT.

Flow rates: In accordance with ANSI Z358.1 all editions - Shower: 105-114L/min. Eyewash: 9.8L/min



- Model
- Description

F-590

Trace Heated Freeze Protected Drench Shower/Eye Wash technical data:

The F-590 provides effective protection in areas exposed to -25 C/-13 F. Heat trace tape is applied directly to the interior piping which is further surrounded by polyurethane insulation and a poly fiber outer sleeve for added thermal protection.

Head: 10" ABS plastic of Safety Yellow color, ABS plastic eye wash of Safety green color.

Valves: Shower valve of 1" corrosion-resistant 304SS ball valve. Eyewash valve of 3/4" corrosion-resistant 304SS ball valve.

Water supply: 1" IPT.

Flow control: In accordance with ANSI Z358.1 all editions - Shower: 105-114L/min. **Eyewash:** 9.8L/min

Hydraulic pressure: 0.2MPA-0.8MPA Voltage

Voltage: 220V-250V



- Model
- Description

F-SL-509

Portable Shower/Eyewash data:

The F-SL-509 is a wheeled, insulated, portable shower and eye wash station that can operate for 6-10 hours when fully charged (12 V DC) - or continuously (220V). The unit offers limited heated water storage with a 3/4" water attachment inlet to feed potable water into and through the unit from another source; water instantly commences being heated to the thermostat setting with a 3-6 hour heating timeline.

Size: 20"W x 16"D x 46"H (503x400x1165mm)

Charging time: 3-6 hours

Water storage tank: 11 gallons/ 45L.

Flow control: 1.25 - 2 gpm/ 5-8 LPM. In accordance with ANSI Z358.1 all editions

Temperature control: 15 - 45 C



- Model
- Description

F-SL-602

Stainless Steel Polar Shower Booth F-SL-602:

Size: 48"W x 36"D x 87"H (1200 W x D900 x H 2200mm)

Head: 10" 304SS shower head, ABS eye wash head, 10"SS bowl.

Valves: Shower valve = 1" 304SS ball valve. Eye wash valve= 1/2" 304SS ball valve

Shower Head/Eyewash: 10" ABS plastic of Safety Yellow color

Valves: 1" corrosion-resistant 304SS ball valve. Eyewash valve of 1/2" corrosion-resistant 304SS ball valve.

Water supply and outlet: 1 1/4" IPT.

Flow control: Max 28.5 gpm/114L/Min. In accordance with ANSI Z358.1 all editions - Shower: 105-114L/min.

Hydraulic pressure: 30 psi - 115 psi/0.2MPA - 0.8MPA

Benefit: Eye Wash & Shower option for almost every industrial situation. Please choose the optional 316SS model for highly acidity applications - priced P.O.A.



- Model
- Description

F-SL-570

Portable Eye Wash Unit technical data:

Pressurized portable eye wash station for remote locations offering more than 10 minutes of use.

Material: 304SS

Size: 13"D x 38"H (325 x 950mm)

Operating temperature: -5 - 45 Degrees

Pressurize: Using air pressure valve pressurize canister to 90 psi/0.6MPA.

Water: Place potable water into the bottle from the top - max capacity is 11.25 gallons/45L.

In accordance with ANSI Z358.1 all editions

Options: (carrying handle or insulated outer sleeve priced P.O.A.)